

RECEIVED
CENTRAL FAX CENTER

NOV 16 2006

Listing of Claims:

1. (original) A device (10; 110) for clamping a workpiece (50, 50a, 50b, 50c 50d; 150d) on a rotatably drivable longitudinal axis having:

- a tensioning spindle (12; 112)
- a counter-holder (14; 114) and
- a carrier,

at least the tensioning spindle (12; 112) being mounted such that it is rotatable about the longitudinal axis (A), and

the carrier being fixed to the tensioning spindle (12; 112) and, when the workpiece (50, 50a, 50b, 50c, 50d; 150d) is clamped between the tensioning spindle (12; 112) and the counter-holder (14; 114), being capable of being brought into engagement with the workpiece (50, 50a, 50b, 50c, 50d; 150d) in such a way that it transmits a rotary movement of the tensioning spindle (12; 112) to the workpiece (50, 50a, 50b, 50c, 50d; 150d),

the carrier having a spring element (30; 130),

characterised by an adapter element (58; 158) which is constructed to be fixed to the workpiece (50, 50a, 50b, 50c, 50d; 150d) and which cooperates with the tensioning spindle (12; 112) to clamp the workpiece (50, 50a, 50b, 50c, 50d; 150d), the spring element (30; 130) acting on the adapter element (58, 58a, 58b, 58c, 58d; 158d) under prestress to transmit a torque or being capable of being brought into engagement with said adapter element.

2. (currently amended) ~~A device (10; 110) according to Claim 1~~ A device (10; 110) for clamping a workpiece (50, 50a, 50b, 50c 50d; 150d) on a rotatably drivable longitudinal axis having:

- a tensioning spindle (12; 112)
- a counter-holder (14; 114) and
- a carrier,

at least the tensioning spindle (12; 112) being mounted such that it is rotatable about the longitudinal axis (A), and

Amendment Response
Serial No. 10/549,298 Group Art Unit 3722
Atty. Docket No. 16164-124
Page 2 of 9

the carrier being fixed to the tensioning spindle (12; 112) and, when the workpiece (50, 50a, 50b, 50c, 50d; 150d) is clamped between the tensioning spindle (12; 112) and the counter-holder (14; 114), being capable of being brought into engagement with the workpiece (50, 50a, 50b, 50c, 50d; 150d) in such a way that it transmits a rotary movement of the tensioning spindle (12; 112) to the workpiece (50, 50a, 50b, 50c, 50d; 150d).

the carrier having a spring element (30; 130).

characterised by an adapter element (58; 158) which is constructed to be fixed to the workpiece (50, 50a, 50b, 50c, 50d; 150d) and which cooperates with the tensioning spindle (12; 112) to clamp the workpiece (50, 50a, 50b, 50c, 50d; 150d), the spring element (30; 130) acting on the adapter element (58, 58a, 58b, 58c, 58d; 158d) under prestress to transmit a torque or being capable of being brought into engagement with said adapter element; and,

characterised in that the spring element comprises a leaf spring (30; 130) which, at one end, is fixed to the tensioning spindle (12; 112) and, at its free end, is constructed with an engagement element (36; 136), the engagement element (36; 136) being capable of deflection and of being brought into torsion-resistant engagement with the workpiece (50, 50a, 50b, 50c, 50d; 150d).

3. (original) A device (10; 110) according to Claim 2, characterised in that the leaf spring (30; 130) is received and fixed with form fit in a radial or axial cutout (28; 128) in the tensioning spindle (12; 112).

4. (previously amended) A device (10; 110) according to Claim 2, characterised in that the leaf spring (30; 130) has a width (B, b) which is a multiple of the height (H).

5. (previously amended) A device (10) according to Claim 2, characterised in that the leaf spring (30) tapers in the axial direction.

6. (previously amended) A device (10) according to Claim 2, characterised in that the engagement element (36) tapers.

7. (previously amended) A device (10; 110) according to Claim 2, characterised in that the engagement element (10; 110) is constructed in the form of a multi-stepped cone (38; 40), the cone angles (α , β) increasing with the increasing spacing from the free end of the leaf spring (30; 130).

8. (original) A device according to Claim 1, characterised in that the spring element comprises a pressure spring which, at its free end, is constructed with an engagement body.

9. (currently amended) ~~A device according to Claim 8,~~ A device (10; 110) for clamping a workpiece (50, 50a, 50b, 50c, 50d; 150d) on a rotatably drivable longitudinal axis having:

- a tensioning spindle (12; 112)
- a counter-holder (14; 114) and
- a carrier,

at least the tensioning spindle (12; 112) being mounted such that it is rotatable about the longitudinal axis (A), and

the carrier being fixed to the tensioning spindle (12; 112) and, when the workpiece (50, 50a, 50b, 50c, 50d; 150d) is clamped between the tensioning spindle (12; 112) and the counter-holder (14; 114), being capable of being brought into engagement with the workpiece (50, 50a, 50b, 50c, 50d; 150d) in such a way that it transmits a rotary movement of the tensioning spindle (12; 112) to the workpiece (50, 50a, 50b, 50c, 50d; 150d),

the carrier having a spring element (30; 130),

characterised by an adapter element (58; 158) which is constructed to be fixed to the workpiece (50, 50a, 50b, 50c, 50d; 150d) and which cooperates with the tensioning spindle (12; 112) to clamp the workpiece (50, 50a, 50b, 50c, 50d; 150d), the spring element (30; 130) acting on the adapter element (58, 58a, 58b, 58c, 58d; 158d) under

Amendment Response

Serial No. 10/549,298 Group Art Unit 3722

Atty. Docket No. 16164-124

Page 4 of 9

prestress to transmit a torque or being capable of being brought into engagement with said adapter element.

in that the spring element comprises a pressure spring which, at its free end, is constructed with an engagement body.

characterised in that the pressure spring and the engagement body are at least partially received in a receiving bore in the tensioning spindle or the counter-holder and are displaceable in said receiving bore with compression of the pressure spring.

10. (previously amended) A device (110) according to Claim 1, characterised in that the spring element (130) can be deflected in the axial direction.

11. (previously amended) A device (10) according to Claim 1, characterised in that the spring element (30) can be deflected in the radial direction.

12. (previously amended) A device (10; 110) according to Claim 1, characterised in that the tensioning spindle (12; 112) and/or the counter-holder (14; 114) each have a centring cone.

13. (original) A device (10; 110) according to Claim 12, characterised in that the centring cone has a centring cone angle in the range between 45° and 75°, preferably between 55° and 65°, particularly preferably of 60°.

14. (previously amended) A device (10; 110) according to Claim 1, characterised in that the counter-holder (14; 114) can be displaced and fixed in the axial direction.

15. (currently amended) ~~A device (10; 110) according to Claim 1,~~ A device (10; 110) for clamping a workpiece (50, 50a, 50b, 50c, 50d; 150d) on a rotatably drivable longitudinal axis having:

- a tensioning spindle (12; 112)
- a counter-holder (14; 114) and

Amendment Response

Serial No. 10/549,298 Group Art Unit 3722

Atty. Docket No. 16164-124

Page 5 of 9

- a carrier.

at least the tensioning spindle (12; 112) being mounted such that it is rotatable about the longitudinal axis (A), and

the carrier being fixed to the tensioning spindle (12; 112) and, when the workpiece (50, 50a, 50b, 50c, 50d; 150d) is clamped between the tensioning spindle (12; 112) and the counter-holder (14; 114), being capable of being brought into engagement with the workpiece (50, 50a, 50b, 50c, 50d; 150d) in such a way that it transmits a rotary movement of the tensioning spindle (12; 112) to the workpiece (50, 50a, 50b, 50c, 50d; 150d),

the carrier having a spring element (30; 130),

characterised by an adapter element (58; 158) which is constructed to be fixed to the workpiece (50, 50a, 50b, 50c, 50d; 150d) and which cooperates with the tensioning spindle (12; 112) to clamp the workpiece (50, 50a, 50b, 50c, 50d; 150d), the spring element (30; 130) acting on the adapter element (58, 58a, 58b, 58c, 58d; 158d) under prestress to transmit a torque or being capable of being brought into engagement with said adapter element,

characterised in that the adapter element (58; 158) has an engagement groove (70; 170) which can be brought into torque-transmitting engagement with the engagement element (36; 136) or engagement body.

16. (currently amended) ~~A device according to Claim 1,~~ A device (10; 110) for clamping a workpiece (50, 50a, 50b, 50c 50d; 150d) on a rotatably drivable longitudinal axis having:

- a tensioning spindle (12; 112)

- a counter-holder (14; 114) and

- a carrier,

at least the tensioning spindle (12; 112) being mounted such that it is rotatable about the longitudinal axis (A), and

the carrier being fixed to the tensioning spindle (12; 112) and, when the workpiece (50, 50a, 50b, 50c, 50d; 150d) is clamped between the tensioning spindle (12; 112) and the counter-holder (14; 114), being capable of being brought into engagement with the

Amendment Response

Serial No. 10/549,298 Group Art Unit 3722

Atty. Docket No. 16164-124

Page 6 of 9

workpiece (50, 50a, 50b, 50c, 50d; 150d) in such a way that it transmits a rotary movement of the tensioning spindle (12; 112) to the workpiece (50, 50a, 50b, 50c, 50d; 150d),
the carrier having a spring element (30; 130),
characterised by an adapter element (58; 158) which is constructed to be fixed to the workpiece (50, 50a, 50b, 50c, 50d; 150d) and which cooperates with the tensioning spindle (12; 112) to clamp the workpiece (50, 50a, 50b, 50c, 50d; 150d), the spring element (30; 130) acting on the adapter element (58, 58a, 58b, 58c, 58d; 158d) under prestress to transmit a torque or being capable of being brought into engagement with said adapter element,

characterised in that, at its outer circumference, the adapter element (58; 158) is constructed with a gripper channel (68; 168) in which an external gripper can engage to transport the adapter element (58; 158).